

MPC702-200

STEP NUMBERS FOR CHROMED PARTS 10

STEP NUMBERS FOR NON-CHROMED PARTS 10

PART NUMBERS 37

CEMENT ----->

DO NOT CEMENT ----->

CLEAR PLASTIC PARTS CLEAR

RED CLEAR PLASTIC PARTS RED CLEAR

IMPORTANT! READ THESE INSTRUCTIONS FIRST.

Before you begin building your kit, read the instructions and study the illustrations carefully. Test fit the parts before cementing them together, to acquaint yourself with their proper location. It is best to cut the parts from the "runners" with a modeler's knife instead of twisting them off. Cut the parts only as they're needed. Only paint and cement made for styrene should be used. Trim off excess plastic or "flash". The plating should be scraped from the chromed parts where they are to be cemented. Use cement sparingly. Apply cement to small parts with a toothpick. When painting your model, it is best to cement all non-chromed parts to the body and paint the whole unit at one time.

1

105 STOCK OR 108 CUSTOM

10

12

2

DO NOT CEMENT

NOTE: Repeat for other side.

Front

2

105 STOCK OR 108 CUSTOM

11

NOTE: Repeat for other side.

Rear

11

35

Repeat for other side

DO NOT CEMENT

8

6

100

103L

103R

101FL

101

2

Repeat for other side using 101FR

12

61

6

109

2

RED CLEAR

Repeat for other side

41

102RL

102

3

Repeat for other side using 102RR

4

19

6

2

17

16

1

31

30

7

18

3

4

5

32

NOTE: Repeat for other side.

5

26

27

2

6

107

39

1

22

21

3

4

7

4

3

2

7

123

1

3

2

NOTE: Repeat for other side.

8

33

37

2

1

3

29

4

34

13

MOTORCYCLE

52

4

53

118

5

6

126

121

8

51

1

51

7

119

113

9

10

Repeat for other side using 112

14

114

REMOVE

110

2

REMOVE

111

DO NOT CEMENT

54

3

125

10

50

6

CEMENT OPTIONAL

57

DO NOT CEMENT

56

4

5

49

8

CEMENT OPTIONAL

58

9

9

7

24

4

3

38

5

59

6

★

Cement here only.

1

2

Metal Axle

NOTE: Repeat steps 1 and 2 for other side.

★ NOTE: Locate to tail pipe engraved on the underside of chassis.

10

1

REMOVE

5

6

7

3

60

4

2

If T Top is to be used, cut along score lines on inside of roof.

CAUTION: When using a modeler's knife, be extremely careful. Adult supervision is recommended.

If T Top is being used, remove bars from window by cutting along score lines.

Part no. 60 is to be used only if T Top is being used.

15

1

42

2

43

44

3

45

DO NOT CEMENT

55

6

Repeat for other side

5

47

Repeat for other side

46

4

16

DECAL PLACEMENT

NOTE: For ease of applying your decals, they are separated on the sheet.

For the experienced modeler, you may still use a modeler's knife and cut close to the image, and for the novice you can cut them apart with scissors.

When applying decals, be sure to follow the instructions exactly as written.

APPLICATION INSTRUCTIONS

1. Refer to box art and instruction sheet for decal locations.
2. Cut decals apart close to image.
3. Dip into water for a minimum of 20 seconds, maximum of 2 minutes.
4. Moisten model where decals are to be applied, to aid in positioning.
5. Remove decal from water when loose, and slide from paper backing onto model.
6. Thoroughly blot out excess water, air bubbles, and any excess emulsion with soft, lint-free cloth.
7. Allow time to dry before handling.

Repeat for other side using 102RR

102

102RL

41

1

3

2

61

6

109

RED CLEAR

Repeat for other side

5

114

REMOVE

110

2

REMOVE

111

DO NOT CEMENT

54

3

125

10

50

6

CEMENT OPTIONAL

57

DO NOT CEMENT

56

4

5

49

8

CEMENT OPTIONAL

58

9